

NOTES:

- (1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.
- (2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.
- (3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.
- (4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

A

A

Ø96in
[2438.4mm]
SPRAY DIAMETER

Ø25 1/2in
[647.70mm]

B

B

C

C

14in
[355.6mm]
TYP

125in
[3175.0mm]
SPRAY HEIGHT

ANCHOR PATTERN

D

D

31in
[789.97mm]

1/2" (13mm) X 8" (203mm) 316SS
THREADED ROD C/W FENDER WASHER,
LOCK WASHER & NUT (X4), MINIMUM
6" (152mm) EMBEDMENT. EPOXY SET
ANCHOR ADHESIVE
TO BE PROVIDED BY CONTRACTOR

1" (25mm) HOSE
SUPPLIED BY EMPEX.

2" (50mm) COUPLING
2" (50mm)-1" (25mm) REDUCER
1" (25mm) HOSEBARB W/SS CLAMP
TO BE PROVIDED BY CONTRACTOR

WATERFEED
2" (50mm) PVC SCH 40 PIPE
EXTENDED 6" (152mm) ABOVE POOL SLAB.

6in [152mm]

8in [203mm]

F

F

Notes: Overall dimensions of toys are approximate.
Approximate Weight: 46lbs / 20.9kgs

© EMPEX WATERTOYS



WATER SUPPLY
20 gpm @ 25 psi
1.3L/S @17.5m

AQUABLIP DOLCE

AD930

11/02/2022

SCALE:

Sheet
1 of 1