

1

1

2

1

3

1

4

NOTES:

- (1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.
- (2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.
- (3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.
- (4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX PERFORATIONS. 1#32" (0.8mm)

A

A

B

B

C

C

D

D

E

E

F

F

ø60in
[1524.0mm]
SPRAY DIAMETER
NOT TO SCALE

30 5/8in
[777.9mm]

76 3/4in
[1949.5mm]

4 3/4in
[120.7mm]
TYP

FLANGE DETAIL

21 1/8in
[537.1mm]

57 3/8in
[1457mm]

- (3) LOWER TOY AND BOLT TO INSERTS.
- (2) MAKE PLUMBING CONNECTION.
- (1) BOLT INTSERTS.

1/2" (13mm) STAINLESS STEEL (316) THREADED ROD, WASHER, LOCK WASHER, & NUT. SUGGESTED 7" (180mm) THREADED ROD WITH 5" (150mm) EMBEDMENT. TO BE PROVIDED BY CONTRACTOR

- 1" (25mm) ø HOSE (SUPPLIED BY EMPEX)
- 2" (50mm) COUPLING
- 2" (50mm) - 1" (25mm) REDUCER
- 1" (25mm) HOSEBARB W/ SS CLAMP TO BE PROVIDED BY CONTRACTOR

8in [203.1mm]

2" (50mm)
WATER FEED

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY
30 gpm @ 25 psi
1.89L/S @17.5m

AQUAVROOM #4

AM104

15/05/2020

SCALE:

Sheet 1 of 1

1

2

3

4