

NOTES:

- (1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.
- (2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.
- (3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.
- (4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

LOWER TOY AFTER BASE PORTION IS ANCHORED TO GROUND.


STAINLESS STEEL (316)
 5/8" (16mm) THREADED ROD, WASHER, LOCK WASHET, & NUT.
 THREADED ROD LENGTH 7" (180mm) WITH 6" (150mm) EMBEDMENT.
 USE MINIMUM 6 ANCHORS.

2"(50mm) SCH 40 PVC WATERFEED TO BE EXTENDED 8" (200mm) ABOVE SLAB.

1"(25mm) FLEX HOSE PROVIDED BY EMPEX.

2" (50mm)-1" (25mm) FITTING AND HOSE CLAMP TO BE PROVIDED BY CONTRACTOR.

[203mm]
8in



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY
 30 gpm @ 25 psi
 1.89L/S @ 17.5m

AQUACLUNE

CL302

11/4/2014

SCALE:
1:25

Sheet
1 of 1