

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

[6090mm]
Ø 240in
SPRAY DIAMETER
NOT TO SCALE

[622mm]
Ø 25in

[429mm]
16.9in

[371mm]
14.6in

[214mm]
8.4in

FLANGE DETAIL

1" (25mm) HOSE
SUPPLIED BY EMPEX

2" (50mm) TO 1" (25mm)
REDUCER TO BE
PROVIDED BY
CONTRACTOR.

STAINLESS STEEL (316)
Ø 5/8" (16mm) THREADED ROD,
WASHER, LOCK WASHER, & NUT.
9" (230mm) THREADED ROD LENGTH
WITH 6" (150mm) EMBEDMENT.
MINIMUM 6 ANCHORS.

[203mm]
8in

2" (50mm) PVC SCH 40
WATERFEED TO BE EXTENDED
8" (200mm) ABOVE SLAB.

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY
30 gpm @ 25 psi
1.89L/S @ 17.5m

AQUASPINZ

K305

9/17/2014

SCALE:
1:30

Sheet
1 of 1