

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

A

A

B

B

C

C

D

D

E

E

F

F

[1829mm]  
Ø 72in  
SPRAY DIAMETER

[608mm]  
Ø 24in

[2283mm]  
90in

[769mm]  
30in

[241.7mm]  
9.5in

[92.5mm]  
3.6in

[170.9mm]  
6.7in

FLANGE DETAIL

1" (25mm) FLEX HOSE PROVIDED BY EMPEX

2" (50mm) TO 1" (25mm) REDUCER TO BE PROVIDED BY CONTRACTOR.

[203mm]  
8in

LOWER FLANGE COVER AFTER INSTALL.

STAINLESS STEEL (316) Ø 1/2" (13mm) THREADED ROD, WASHER, LOCK WASHER, & NUT. 7" (180mm) THREADED ROD LENGTH WITH 5" (120mm) EMBEDMENT. INSTALL MINIMUM 5 ANCHORS.

2" (50mm) PVC SCH 40 WATER FEED EXTENDED 6" (150mm) ABOVE SLAB.



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY

30 gpm @ 25 psi  
1.89L/S @ 17.5m

**AQUAZING LARGE**

**K601L**

8/23/2016

SCALE:  
1:20

Sheet  
1 of 1