

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

[2438mm] ϕ 96in
SPRAY DIAMETER
NOT TO SCALE

[622mm]
25in

[851mm]
34in

[356mm]
14in
TYP X 3 @ 60°

[1219mm]
48in
SPRAY HEIGHT
NOT TO SCALE

[306mm]
12in

LOWER TOY ONCE BASE IS ANCHORED TO THE GROUND.

1" (25mm) HOSE SUPPLIED BY EMPEX.

1/2" (13mm) STAINLESS STEEL (316) THREADED ROD, WASHER, LOCK WASHER, & NUT. SUGGESTED 7" (180mm) THREADED ROD WITH 6" (150mm) EMBEDMENT.

2" (50mm) TO 1" (25mm) REDUCER TO BE SUPPLIED BY CONTRACTOR.

2" (50mm) PVC SCH 40 PIPE EXTENDED 4" (100mm) ABOVE POOL SLAB.

[203mm]
8in



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY
15 gpm @ 5 psi
1 L/S @ 3.5m

AQUAORC

M501

11/4/2014

SCALE:
1:20

Sheet
1 of 1