

NOTES:

- (1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.
- (2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.
- (3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.
- (4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX PERFORATIONS. 1#32" (0.8mm)

Ø72in [1828.8mm]  
SPRAY DIAMETER

Ø12 3/4in [Ø323.9mm]

20 7/8in [531.3mm]

96 1/4in [2446.1mm]

Ø11" [279.4mm] o/s

Flange Cover Ø12.7500

11.0" [279mm]

9.5" [240mm] o/c

LOWER FLANGE COVER AFTER INSTALL

ENSURE LEVEL SURFACE INSTALL 6" (152mm) X 1/8" (3mm) GASKET PROVIDED BY EMPEX

2" (50mm) FEED PIPE CUT CLOSE TO ALLOW FULL DRAINAGE (WINTERIZATION)

FLOODED COLUMN

8in [202.3mm]

STAINLESS STEEL (316)  
Ø1/2" (13mm) TREADED ROD  
WASHER, LOCKWASHER & NUT  
7" (180mm) TREADED ROD LENGTH  
WITH 5" (120mm) EMBEDMENT.  
INSTALL MINIMUM 5 ANCHORS.  
TO BE PROVIDED BY CONTRACTOR

2" (50mm) S40 PVC PIPE  
WATERFEED



Notes: Overall dimensions of toys are approximate.  
Approximate Weight: 72lbs / 32.7kgs

© EMPEX WATERTOYS

WATER SUPPLY  
30 gpm @ 25 psi  
1.89L/S @ 17.5m

AQUAWIGL

T272

03/09/2020

SCALE:

Sheet  
1 of 1