

1

2

3

4

## NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX  $1\frac{1}{32}"$  (0.8mm) PERFORATIONS.

[2956mm]

116in

[603mm]  
24in[852mm]  
34in6in (150mm)-12in (300mm)  
WATER DEPTH.

[6096mm]

240in

SPRAY DISTANCE NOT TO SCALE

[203mm]  
8in

5/8" STAINLESS STEEL (316)  
THREADED ROD, WASHER,  
LOCK WASHER, & NUT.  
9" THREADED ROD LENGTH  
WITH 6" (150mm) EMBEDMENT.  
INSTALL MINIMUM 6 ANCHORS.

[429mm]  
Ø 16.9in[214mm]  
8.4in[371mm]  
14.6in

FLANGE DETAIL



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY  
NO EXTERNAL SUPPLY

**WATERTOTTER****T311**

11/5/2014

SCALE:  
1:25Sheet  
1 of 1

1

2

3

4