

1

2

3

4

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX $1\frac{1}{32}$ " (0.8mm) PERFORATIONS.

A

A

B

B

C

C

D

D

E

E

F

F

[324mm] 13in

[1829mm] 72in

[1784mm] 70in

LOWER FLANGE COVER AFTER INSTALLATION.

[1183mm] 47in

[1046mm] 41in

2"(50mm) TO 1"(25mm) REDUCER TO BE PROVIDED BY CONTRACTOR.

1" (25mm) FLEX HOSE PROVIDED BY EMPEX.

STAINLESS STEEL (316) $\varnothing 1/2$ " (13mm) THREADED ROD, WASHER, LOCK WASHER, & NUT.
6" (150mm) THREADED ROD WITH 4" (100mm) EMBEDMENT. INSTALL MINIMUM 6 ANCHORS PER LEG.

[200mm] 8in

2" (50mm) PVC SCH 40 WATERFEED EXTENDED 6" (150mm) ABOVE POOL SLAB.

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY

30 gpm @ 25 psi
1.89L/S @ 17.5m

AQUAFORM

T371

9/10/2014

SCALE:
1:25

Sheet
1 of 1

1

2

3

4