

1

2

3

4

**NOTES:**

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

[610mm]  
Ø24in  
SPRAY DIAMETER

[622mm]  
Ø25in

[1697mm]  
67in

[1697mm]  
67in

[3209mm]  
126in

[432mm]  
17in

[216mm] [374mm]  
8.5in 14.7in

[112mm]  
4.4in

FLANGE DETAIL

LOWER FLANGE COVER AFTER TOY IS INSTALLED.

STAINLESS STEEL (316)  
5/8" (16mm) THREADED ROD, WASHER, LOCK WASHER, & NUT.  
THREADED ROD LENGTH 9" (230mm) WITH 6" (150mm) EMBEDMENT. USE MINIMUM 6 ANCHORS.

2" (50mm) PVC SCH 40 WATER FEED

2" (50mm) FLEX HOSE PROVIDED BY EMPEX.

2" (50mm) FITTING AND HOSE BARB TO BE SUPPLIED BY CONTRACTOR.

2" (50mm) SCH 40 PVC WATERFEED TO BE EXTENDED 8" (203mm) ABOVE SLAB.

[203mm]  
8in



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY

70 gpm @ 25 psi  
4.4L/S @ 17.5m

**AQUAFALL W/DIVERTER**

**T730**

6/25/2015

SCALE:  
1:35

Sheet  
1 of 1

1

2

3

4

F

F