

1

2

3

4

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

[3505mm]
Ø 138in
SPRAY DIAMETER

[2154mm]
85in

[1865mm]
73in

[429mm]
16.9in

[371mm] [214mm]
14.6in 8.4in

[111mm]
4in

FLANGE DETAIL

[3762mm]
148in

LOWER FLANGE COVER AFTER TOY IS INSTALLED.

STAINLESS STEEL (316)
5/8" (16mm) THREADED ROD, WASHER,
LOCK WASHER, & NUT.
THREADED ROD LENGTH 9" (230mm)
WITH 6" (150mm) EMBEDMENT. USE
MINIMUM 6 ANCHORS.

2" (50mm) SCH 40 PVC
WATERFEED TO BE EXTENDED
8" (200mm) ABOVE SLAB.

2" (50mm) FLEX HOSE
PROVIDED BY EMPEX.

2" (50mm) FITTING AND HOSE
BARB TO BE SUPPLIED
BY CONTRACTOR.

[203mm]
8in

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY
70 gpm @ 25 psi
4.4L/S @ 17.5m

AQUAFALLS

T733

9/17/2014

SCALE:
1:50

Sheet
1 of 1

1

2

3

4

A

A

B

B

C

C

D

D

E

E

F

F