

**NOTES:**

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

A

A

B

B

C

C

D


D

E

E

F

F



FLANGE DETAIL

[356mm]  
14in  
TYPx2

[1524mm]  
60in  
SPRAY HEIGHT

[1981mm]  
78in  
SPRAY DISTANCE

[648mm]  
Ø26in

[724mm]  
29in

[568mm]  
22in

[1335mm]  
53in

AFTER WATER CONNECTION IS COMPLETE, BOLT DOME TO AQUAPIP BASE.

2"(50mm)-1"(25mm) FITTING AND HOSE CLAMP PROVIDED BY CONTRACTOR.

1"(25mm) FLEX HOSE PROVIDED BY EMPEX.

STAINLESS STEEL (316) THREADED ROD, LOCK WASHER, WASHER, & NUT. THREADED ROD LENGTH 7" (180mm) WITH 6" (150mm) EMBEDMENT.

[203mm]  
8in

2"(50mm) SCH 40 PVC WATERFEED TO BE EXTENDED 8"(200mm) ABOVE SLAB.

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



**WATER SUPPLY**

30 gpm @ 5 psi  
1.89L/S @3.5m

**AQUAPIP**

**T804**

11/5/2014

SCALE:  
1:20

Sheet  
1 of 1