

1

2

3

4

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

A

A

[622mm]
Ø 25in

[914mm]

36in

SPRAY DIAMETER

[1643mm]
65in

B

B

[1643mm]
65in

[374mm]
14.7in

[216mm]
8.5in

[432mm]
17.0in

FLANGE DETAIL

C

C

D

D

[3338mm]
131in

2" (50mm)-1/2" (13mm) FITTING AND HOSE BARB TO BE SUPPLIED BY CONTRACTOR.

STAINLESS STEEL (316) 5/8" (16mm) THREADED ROD, WASHER, LOCK WASHER, & NUT. THREADED ROD LENGTH 9" (230mm) WITH 6" (150mm) EMBEDMENT. USE MINIMUM 6 ANCHORS.

LOWER FLANGE COVER AFTER TOY IS INSTALLED.

1/2" (13mm) FLEX HOSE PROVIDED BY EMPEX.

E

E

2" (50mm) SCH 40 PVC WATERFEED TO BE EXTENDED 8" (200mm) ABOVE SLAB.

[203mm]
8in

F

F



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY

10 gpm @ 25 psi
0.63 L/S @ 17.5m

AQUADUNK DILLO

T816-D

5/3/2017

SCALE:
1:25

Sheet
1 of 1

1

2

3

4