

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

[1829mm]
Ø 72in
SPRAY DIAMETER

[647.70mm]
Ø 25.50in

[457mm]
18in

[2566mm]
101in

[1609mm]
63in

[857mm]
33.75in

LOWER AND SECURE TOP SECTION TO BASE

MOUNT BASE TO CONCRETE
STAINLESS STEEL (316)
1/2" (13mm) THREADED ROD,
WASHER, LOCK WASHER, & NUT.
THREADED ROD LENGTH 7" (180mm)
WITH 6" (150mm) EMBEDMENT.

2" (50mm) PVC SCH 40
WATER FEED TO BE EXTENDED
8" (200mm) ABOVE SLAB.

1" (25mm) FLEX HOSE
PROVIDED BY EMPEX

2" (50mm)-1" (25mm) FITTING
AND HOSE BARB TO BE SUPPLIED
BY CONTRACTOR.

[203mm]
8in

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY
30 gpm @ 25 psi
1.89L/S @ 17.5m

AQUADOO

T932

10/5/2016

SCALE:
1:25

Sheet
1 of 1