

1

2

3

4

**NOTES:**

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

[2134mm]  
Ø84in  
SPRAY DIAMETER NTS

[622mm]  
Ø25in

[242mm]  
9.5in

[171mm]  
6.7in

[92mm]  
3.6in

FLANGE DETAIL

[1651mm]  
65in  
SPRAY HEIGHT

[884mm]  
35in

LOWER TOY ONCE FLANGE IS INSTALLED.

1/2" (13mm) STAINLESS STEEL (316) THREADED ROD, WASHER, LOCK WASHER, & NUT. SUGGESTED 7" (180mm) THREADED ROD WITH 6" (150mm) EMBEDMENT.

1" (25mm) HOSE SUPPLIED BY EMPEX.

2" (50mm) TO 1" (25mm) REDUCER TO BE SUPPLIED BY CONTRACTOR.

2" (50mm) PVC SCH 40 PIPE EXTENDED 4" (100mm) ABOVE POOL SLAB.

[203mm]  
8in

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



**WATER SUPPLY**  
20 gpm @ 25 psi  
1.3L/S @ 17.5m

# AQUACAP

TR269L

11/5/2014

SCALE:  
1:20

Sheet  
1 of 1

1

2

3

4

A

A

B

B

C

C

D

D

E

E

F

F