

1

2

3

4

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

A

A

[3658mm]  
Ø 144in  
SPRAY DIAMETER

[1216mm]  
48in

[777mm]  
31in

B

B

[371mm]  
14.6in


[214mm]  
8.4in

[429mm]  
16.9in

FLANGE DETAIL

C

C



[3427mm]  
135in

D

D

LOWER FLANGE COVER AFTER TOY IS INSTALLED.

STAINLESS STEEL (316)  
5/8" (16mm) THREADED ROD, WASHER, LOCK WASHER, & NUT.  
THREADED ROD LENGTH 9" (230mm) WITH 6" (150mm) EMBEDMENT. USE MINIMUM 6 ANCHORS.

1 1/2" (38mm) FLEX HOSE PROVIDED BY EMPEX.

2" (50mm)-1 1/2" (38mm) FITTING AND HOSE BARB TO BE SUPPLIED BY CONTRACTOR.

2" (50mm) SCH 40 PVC WATERFEED TO BE EXTENDED 8" (200mm) ABOVE SLAB.

2" (50mm) PVC SCH 40 WATER FEED.

[203mm]  
8in

E

E

F

F



Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS

WATER SUPPLY  
60 gpm @ 25 psi  
3.79 L/S @ 17.5m

# AQUABLOOM

TR874

11/5/2014

SCALE:  
1:50

Sheet  
1 of 1

1

2

3

4