

NOTES:

- (1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.
- (2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.
- (3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.
- (4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

SUGGESTED LAYOUT

A

A

B

B

C

C

D

D

E

E

F

F

[7925mm]
312in
SPRAY DISTANCE

[4877mm]
192in

[2438mm]
96in

[1524mm]
60in

[1050mm]
41in
TYP

[6096mm]
240in
SPRAY DISTANCE

[1524mm]
60in

[610mm]
24in
SPRAY HEIGHT
TYP

[241mm]
9.5in

[3048mm]
Ø 120in
SPRAY DIAMETER TYP

[171mm]
6.7in

[92mm]
3.6in

[2542mm]
100in

[2821mm]
111in

[3141mm]
124in

LOWER FLANGE COVER AFTER TOY IS INSTALLED.

1" (25mm) FLEX HOSE PROVIDED BY EMPEX.

2" (50mm)-1" (25mm) FITTING AND HOSE BARB TO BE SUPPLIED BY CONTRACTOR.

2" (50mm) SCH 40 PVC WATERFEED TO BE EXTENDED 8" (20mm) ABOVE SLAB.

T877S (SMALL) T877M (MEDIUM) T877L (LARGE)
STAINLESS STEEL (316)
5/8" (16mm) THREADED ROD, WASHER, LOCK WASHER, & NUT.
THREADED ROD LENGTH 9" (230mm) WITH 6" (150mm) EMBEDMENT. USE MINIMUM 6 ANCHORS.

TYP INSTALLATION DETAIL

[203mm]
8in

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY
30 gpm @ 25 psi
1.89L/S @ 17.5m (EACH TOY)

AQUAFLORA DAISY TRIO

TR877-3

11/6/2014

SCALE:
1:65

Sheet
1 of 1