

NOTES:

(1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.

(2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.

(3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.

(4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1#32" (0.8mm) PERFORATIONS.

[1565mm]  
62in  
APPROX SPRAY AREA

[777mm]  
31in  
APPROX SPRAY AREA

[121mm]  
4.8in  
TYP

FLANGE DETAIL

(3) LOWER TOY AND BOLT TO INSERT.

(2) MAKE PLUMBING CONNECTION.

(1) BOLT INSERT.

1/2" (13mm) STAINLESS STEEL (316) THREADED ROD, WASHER, LOCK WASHER, & NUT. SUGGESTED 7" (180mm) THREADED ROD WITH 5" (150mm) EMBEDMENT.

1" (25mm) Ø HOSE (SUPPLIED BY EMPEX)

2" Ø (50mm) PIPE TO 1" (25mm) Ø HOSE ADAPTOR + CLAMP SUPPLIED BY CONTRACTOR.

[203mm]  
8in

2" (50mm) WATER FEED

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY

30 gpm @ 25 psi  
1.89L/S @ 17.5m

AQUAFOX

Z209

1/19/2018

SCALE:  
1:23

Sheet  
1 of 1