

1

2

3

4

NOTES:

- (1) PURGE ALL WATER SUPPLY LINES TO REMOVE SOLIDS PRIOR TO TOY INSTALLATION.
- (2) PROVIDE ELECTRICAL BOND WITH POOL REBAR.
- (3) INSTALL ALL WATER TOYS PLUMB AND LEVEL.
- (4) PROVIDE STRAINER UPSTREAM OF TOY WITH MAX 1/32" (0.8mm) PERFORATIONS.

A

A

B

B

C

C

D

D

E

E

F

F

ø60in
[1524.0mm]
SPRAY DIAMETER

34 3/4in
[883.3mm]

56 1/4in
[1428.2mm]

4 3/4in
[120.7mm]
TYP

FLANGE DETAIL

37 5/8in
[956.5mm]
SPRAY HEIGHT
NOT TO SCALE

2-WAY DIVERTER

20 1/4in
[514.9mm]

34 7/8in
[885.8mm]

1" (25mm) Ø HOSE
(SUPPLIED BY EMPEX)

2" (50mm) COUPLING
2" (50mm) - 1" (25mm) REDUCER
1" (25mm) HOSEBARB W/ SS CLAMP
TO BE PROVIDED BY CONTRACTOR

8in [203.2mm]

WATERFEED
2" (50mm) PVC SCH 40 PIPE
EXTENDED 6" (152mm) ABOVE SLAB

- (1) BOLT INSERT SLEEVE TO SLAB
- (2) MAKE PLUMBING CONNECTION
- (3) LOWER TOY AND BOLT TO INSERT

1/2" (13mm) X 8" (203mm) 316SS
THREADED ROD, C/W FENDER WASHER
LOCKWASHER & NUT (X4), MINIMUM
6" (152mm) EMBEDMENT, EPOXY SET
ANCHOR ADHESIVE
TO BE PROVIDED BY CONTRACTOR

Notes: Overall dimensions of toys are approximate.

© EMPEX WATERTOYS



WATER SUPPLY

30 gpm @ 25 psi
1.89L/S @17.5m

AQUAVROOM

AM103

15/05/2020

SCALE:

Sheet
1 of 1

1

2

3

4